

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/537,128	06/02/2005	Johannus Leopoldus Bakx	NL021305	8392
24737 7590 08/17/2007 PHILIPS INTELLECTUAL PROPERTY & STANDARDS P.O. BOX 3001			EXAMINER	
			ALI, FARHAD	
BRIARCLIFF MANOR, NY 10510		ART UNIT	PAPER NUMBER	
			2109	·
			MAIL DATE	DELIVERY MODE
		08/17/2007	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

8

	Application No.	Applicant(s)	
	10/537,128	BAKX, JOHANNUS LEOPOLDUS	
Office Action Summary	Examiner	Art Unit	
	Farhad Ali	2109	
The MAILING DATE of this communication app Period for Reply	pears on the cover sheet with the c	orrespondence address	
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period v - Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tin will apply and will expire SIX (6) MONTHS from , cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).	
Status			
1) Responsive to communication(s) filed on <u>02 Jules</u> 2a) This action is FINAL . 2b) This 3) Since this application is in condition for alloware closed in accordance with the practice under Expression 1.	action is non-final. nce except for formal matters, pro		
Disposition of Claims			
4) □ Claim(s) 1-12 is/are pending in the application. 4a) Of the above claim(s) is/are withdraw 5) □ Claim(s) is/are allowed. 6) □ Claim(s) 1-12 is/are rejected. 7) □ Claim(s) is/are objected to. 8) □ Claim(s) are subject to restriction and/o	wn from consideration.		
Application Papers			
9) The specification is objected to by the Examine 10) The drawing(s) filed on <u>02 June 2005</u> is/are: a) Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Ex	☑ accepted or b)☐ objected to drawing(s) be held in abeyance. See ion is required if the drawing(s) is obj	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).	
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority documents 2. Certified copies of the priority documents 3. Copies of the certified copies of the priority application from the International Bureau * See the attached detailed Office action for a list	s have been received. s have been received in Application rity documents have been received (PCT Rule 17.2(a)).	on No ed in this National Stage	
Attachment(s) Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date 01/20/2006, 06/02/2005.	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal P 6) Other:	ate	

Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 2. Claims 1-7, and 12 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hoeven (US 6,765,858 B2), in view of Pringle (US 4,791,668 A).

<u>Claim 1</u>

Hoeven discloses an arrangement for reading an information carrier, comprising a read head for scanning the information carrier along a scanning path and thereby generating one or more electrical signals in response to a pattern recorded along the scanning path ([Hoeven] Column 2 Lines 29-31, "a read head 4 for scanning the information carrier 2 along a scanning path and thus generating one or more electric signals");

a signal processing unit for processing the one or more electrical signals; electrical conductors for conveying the one or more electrical signals to the signal processing unit ([Hoeven] Column 2 Lines 64-67, "The arrangement further includes electrical conductors 6 for transferring the one or more electric signals V.sub.A-D to a signal processing unit 8").

Hoeven does not disclose the arrangement further comprises controllable termination means for terminating at least one electrical conductor with a selectable

Art Unit: 2109

impedance, the controllable termination means comprising at least two impedances and selecting means for selecting an impedance to terminate the at least one electrical conductor.

Pringle Discloses: Column 1 Lines 5-9, "The invention is concerned with electronic transmission and reception of signals via a transmission line and more particularly pertains to interface circuits which are adaptable to provide more than one terminating or source impedance" and Column 2 Lines 18-21, "A switching device includes at least n switching elements being connected between n of the resistor elements and an input of an amplifier".

It would have been obvious to one of ordinary skill in the art to utilize Hoeven's arrangement for reading an information carrier with Pringle's selectable impedance line interface circuit. Hoeven teaches utilizing a high impedance for data read at comparatively high data speeds and Pringle teaches a circuit which can provide more than one terminating impedance to a given signal. It is desirable to use the proper impedance when reading data using different techniques, therefore it is obvious to have a means for selecting the proper impedance.

Claim 2

Hoeven does not disclose an arrangement as claimed in claim 1 characterized in that the signal processing unit comprises the controllable termination means.

Pringle Discloses: Column 1 Lines 5-9, "The invention is concerned with electronic transmission and reception of signals via a transmission line and more

Art Unit: 2109

particularly pertains to interface circuits which are adaptable to provide more than one terminating or source impedance" and Column 2 Lines 18-21, "A switching device includes at least n switching elements being connected between n of the resistor elements and an input of an amplifier".

It would have been obvious to one of ordinary skill in the art to utilize Hoeven's arrangement for reading an information carrier with Pringle's selectable impedance line interface circuit. Hoeven teaches utilizing a high impedance for data read at comparatively high data speeds and Pringle teaches a circuit which can provide more than one terminating impedance to a given signal. It is desirable to use the proper impedance when reading data using different techniques, therefore it is obvious to have a means for selecting the proper impedance. It is furthermore obvious to incorporate Pringle's selectable impedance line interface circuit into the signal processing unit in order to save space and create one functional unit.

Claim 3

Hoeven does not disclose an arrangement as claimed in claim 1, characterized in that the controllable termination means are able to terminate two or more electrical conductors with different selectable impedances.

Pringle Discloses: Column 1 Lines 5-9, "The invention is concerned with electronic transmission and reception of signals via a transmission line and more particularly pertains to interface circuits which are adaptable to provide more than one terminating or source impedance" and Column 2 Lines 18-21, "A switching device

Art Unit: 2109

includes at least n switching elements being connected between n of the resistor elements and an input of an amplifier".

It would have been obvious to one of ordinary skill in the art to utilize Hoeven's arrangement for reading an information carrier with Pringle's selectable impedance line interface circuit. Hoeven teaches utilizing a high impedance for data read at comparatively high data speeds and Pringle teaches a circuit which can provide more than one terminating impedance to a given signal. It is desirable to use the proper impedance when reading data using different techniques, therefore it is obvious to have a means for selecting the proper impedance. It is furthermore obvious to duplicate the selectable impedance line interface circuit in order to handle multiple signals as doing so produces a predictable result.

Claim 4

Hoeven does not disclose an arrangement as claimed in claim 1, characterized in that the selectable impedance comprises a characteristic impedance of the electrical conductors.

Pringle Discloses: Column 1 Lines 38-41, "A line interface circuit may be adaptable to more than one characteristic impedance by providing metallic contact switches for selecting any one of a plurality of terminating resistances".

It would have been obvious to one of ordinary skill in the art to utilize Hoeven's arrangement for reading an information carrier with Pringle's selectable impedance line interface circuit. Hoeven teaches utilizing a high impedance for data read at

Art Unit: 2109

comparatively high data speeds and Pringle teaches a circuit which can provide more than one terminating impedance to a given signal. It is desirable to use the proper impedance when reading data using different techniques, therefore it is obvious to have a means for selecting the proper impedance. Furthermore, Pringle discloses using a characteristic impedance in the line interface circuit.

Claim 5

An arrangement as claimed in claim 4, characterized in that the controllable termination means are able to select the characteristic impedance when reading the information carrier at a relatively high speed and select a higher impedance when reading the information carrier at a relatively low speed.

Pringle Discloses: Column 2 Lines 32-35, "A control means is connected to the switching device for controlling each of the switching elements to be of one of a high resistance state and a lower resistance state".

It would have been obvious to one of ordinary skill in the art to utilize Hoeven's arrangement for reading an information carrier with Pringle's selectable impedance line interface circuit. Hoeven teaches utilizing a high impedance for data read at comparatively high data speeds and Pringle teaches a circuit which can provide more than one terminating impedance to a given signal. Furthermore, Pringle discloses using a characteristic impedance in the line interface circuit. It is desirable to use the proper impedance when reading data using different techniques, therefore it is obvious to have

Art Unit: 2109

a means for selecting the proper impedance i.e. characteristic (low) impedance for a high reading speed or a high impedance for a low reading speed.

Claim 6

Hoeven discloses an arrangement as claimed in claim 1, characterized in that one or more of the electrical signals are current outputs and in that the selectable impedance functions as a current to voltage converter ([Hoeven] Column 2 Lines 63-64, "A current-voltage converter 48 converts the current signals i.sub.A-D into voltage signals V.sub.A-D").

Claim 7

Hoeven discloses an arrangement as claimed in claim 6, characterized in that the read head performs the scanning by transmitting a radiation beam to the information carrier and receiving a reflected radiation beam from the information carrier, and in that the arrangement further comprises measuring means for measuring the reflectance of the radiation beam, ([Hoeven] Column 2 Lines 45-63, "The read head 4 further has imaging means 42, 43 for imaging the radiation onto the information carrier 2 as a scanning spot 44. The read head 4 further includes imaging means 43, 45, 46 for imaging radiation that leaves the scanning spot 44 onto an optical detector 47. Said imaging means may include, for example, lenses, prisms, lattices, mirrors etc. In the present example, the imaging means comprise a convergent lens 42 and a focusing objective 43 to image the radiation beam generated by the radiation source 41 as a

Art Unit: 2109

scanning spot. Furthermore, a semitransparent mirror 45 is interposed between the convergent lens 42 and the focusing objective 43. Radiation which is reflected from the scanning spot 44 is imaged onto an optical detector 47 via the focusing objective 43, the semitransparent mirror 45 and an astigmatic element 46. The optical detector 47, shown in more detail in FIG. 3, comprises four sub-detectors 47.sub.A, 47.sub.B, 47.sub.C and 47.sub.D. The four sub-detectors 47.sub.A-D each generate a current signal i.sub.A, i.sub.B, i.sub.C, i.sub.D which is indicative of an intensity of the radiation that is incident on the relevant sub-detector").

Hoeven does not disclose that the controllable termination means selects an impedance dependent on the measured reflectance of the radiation beam.

Pringle Discloses: Column 1 Lines 5-9, "The invention is concerned with electronic transmission and reception of signals via a transmission line and more particularly pertains to interface circuits which are adaptable to provide more than one terminating or source impedance" and Column 2 Lines 18-21, "A switching device includes at least n switching elements being connected between n of the resistor elements and an input of an amplifier".

It would have been obvious to one of ordinary skill in the art to utilize Hoeven's arrangement for reading an information carrier with Pringle's selectable impedance line interface circuit. Hoeven teaches utilizing a high impedance for data read at comparatively high data speeds and Pringle teaches a circuit which can provide more than one terminating impedance to a given signal. It is desirable to use the proper impedance when reading data using different techniques, therefore it is obvious to have

Art Unit: 2109

a means for selecting the proper impedance. It is furthermore obvious to select the proper impedance based on the measured reflectance of the radiation beam as it is related to the reading speed which is taught to be monitored by Hoeven.

Claim 12

Hoeven does not disclose a signal processing unit for use in an arrangement according to claim 2.

Pringle Discloses: Column 1 Lines 5-9, "The invention is concerned with electronic transmission and reception of signals via a transmission line and more particularly pertains to interface circuits which are adaptable to provide more than one terminating or source impedance" and Column 2 Lines 18-21, "A switching device includes at least n switching elements being connected between n of the resistor elements and an input of an amplifier".

It would have been obvious to one of ordinary skill in the art to utilize Hoeven's arrangement for reading an information carrier with Pringle's selectable impedance line interface circuit. Hoeven teaches utilizing a high impedance for data read at comparatively high data speeds and Pringle teaches a circuit which can provide more than one terminating impedance to a given signal. It is desirable to use the proper impedance when reading data using different techniques, therefore it is obvious to have a means for selecting the proper impedance. It is furthermore obvious to incorporate Pringle's selectable impedance line interface circuit into the signal processing unit in order to save space and create one functional unit.

Art Unit: 2109

3. Claims 8-11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hoeven (US 6,765,858 B2) as in view of Pringle (US 4,791,668 A), and further in view of Park (US 5,058,130 A).

Claim 8

Hoeven does not disclose an arrangement as claimed in claim 1, characterized in that at least one electrical conductor is terminated with a selectable impedance which is selected by optimizing one or more parameters of the electrical signal conveyed by the at least one electrical conductor.

Park discloses a digital technique for achieving minimal occurrence of jitter, overshoot and undershoot in an output waveform in the filter for digital transmission ([Park] Column 1 Lines 11-15).

It would have been obvious to one of ordinary skill in the art to utilize Hoeven's arrangement for reading an information carrier with Pringle's selectable impedance line interface circuit and Park's digital filtering technique. Hoeven teaches utilizing a high impedance for data read at comparatively high data speeds and Pringle teaches a circuit which can provide more than one terminating impedance to a given signal. It is desirable to use the proper impedance when reading data using different techniques, therefore it is obvious to have a means for selecting the proper impedance.

Furthermore, incorporating Park's filtering techniques to select the desired impedance is

Art Unit: 2109

obvious to one of ordinary skill in the art as it teaches a necessary step needed to select the proper impedance and produces predictable results.

Claim 9, 10, and 11

Claims 9, 10, and 11 are rejected for the reasons stated in Claim 8 above.

Claim Rejections - 35 USC § 112

- 4. The following is a quotation of the first paragraph of 35 U.S.C. 112:
 - The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.
- 5. Claim 12 rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. It is unclear whether applicant is referring to a new signal processing unit or to the unit previously claimed in claim 1.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Farhad Ali whose telephone number is (571) 270-1920. The examiner can normally be reached on Monday thru Friday, 7:30am to 5:00pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Jeffrey C. Pwu can be reached on (571) 272-6798. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2109

Page 12

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

F.A.

JEFFREY PWU SUPERVISORY PATENT EXAMINER